

VAN BEEST BV, Manufacturer/Supplier of wire rope and chain fittings Reg. trade mark 'Green Pin' Van Beest has recently extended its program of Green Pin Polar Shackles with the introduction of three larger sizes of Heavy Duty Polar Shackles. Green Pin Polar Shackles with WLL range from 2 tons up to 85 tons are available for some time already.

Now Polar Shackles with WLL of 120, 150 and 200 tons are also available from stock.

Please find herewith the latest Van Beest product information including details of these new Heavy Duty Polar Shackles. For more information please contact us: sales@vanbeest.nl



bow shackles with safety bolt, for use under extreme climatic conditions

• Material : bow and pin alloy steel, Grade 8 quenched and tempered

• Safety Factor : MBL equals 5 x WLL

• Finish : shackle bow painted silver, pin painted green (120 tons shackle is hot

dipped galvanized)


• Certificates : at no extra charges this product can be supplied with a works certificate, certificate of basic raw material, manufacturer test certificate

and EC Declaration of Conformity. All shackles starting from 150 tons are supplied with a Lloyd's Register of Shipping Certificate on

proof load

• **Note** : +5% forging tolerance on inside width and length

• Temperature Range : -40  $^{\circ}$ C up to + 200 $^{\circ}$ C



| working<br>load<br>limit | diameter<br>bow | diameter<br>pin | diameter<br>eye | width<br>eye | width<br>inside | length<br>inside | width<br>bow | length | length<br>bolt | width | thickness<br>nut | weight<br>each |
|--------------------------|-----------------|-----------------|-----------------|--------------|-----------------|------------------|--------------|--------|----------------|-------|------------------|----------------|
|                          | а               | b               | С               | d            | е               | f                | g            | h      | i              | j     | k                |                |
| tons                     | mm              | mm              | mm              | mm           | mm              | mm               | mm           | mm     | mm             | mm    | mm               | kg             |
| 120                      | 95              | 95              | 215             | 89           | 144             | 381              | 238          | 667    | 440            | 416   | 50               | 110            |
| 150                      | 105             | 108             | 245             | 100          | 165             | 400              | 275          | 702    | 490            | 485   | 60               | 160            |
| 200                      | 120             | 130             | 288             | 110          | 175             | 500              | 290          | 854    | 520            | 530   | 60               | 235            |

## In inch

| working | diameter | diameter | diameter | width   | width                           | length  | width                           | length                          | length   | width                          | thickness | weight |
|---------|----------|----------|----------|---------|---------------------------------|---------|---------------------------------|---------------------------------|----------|--------------------------------|-----------|--------|
| load    | bow      | pin      | eye      | eye     | inside                          | inside  | bow                             |                                 | bolt     |                                | nut       | each   |
| limit   |          |          |          |         |                                 |         |                                 |                                 |          |                                |           |        |
|         | а        | b        | С        | d       | е                               | f       | g                               | h                               | i        | j                              | k         |        |
| tons    | inch     | in a la  | in a la  | in a la | in a la                         | to a la | to a la                         | to a la                         | ton a la | to a la                        | to a la   | 11     |
| tons    | IIICII   | inch     | inch     | inch    | inch                            | inch    | inch                            | inch                            | inch     | inch                           | inch      | lbs    |
| 120     | 3 3/4    | 3 3/4    | 8 1/2    | 3 17/32 | 5 <sup>11</sup> / <sub>16</sub> |         | 9 <sup>11</sup> / <sub>32</sub> | 26 <sup>9</sup> / <sub>32</sub> |          | 16 <sup>3</sup> / <sub>8</sub> | 2         | 243    |
|         |          |          |          |         |                                 |         |                                 |                                 |          |                                |           |        |

VAN BEEST BV P.O. Box 57 3360 AB Sliedrecht The Netherlands Industrieweg 6 3361 HJ Sliedrecht

Telephone +31 184 41 33 00
Telefax +31 184 41 49 59
E-mail sales@vanbeest.nl
Internet www.vanbeest.nl



